

Dell 22 Monitor | P2217H

Display

Diagonally Viewable Size:

54.61 cm (21.5 Inches)

Preset Display Area(H x V):

476.06 mm x 267.79 mm

18.74" x 10.54"

127484.10 mm² (197.6 inches²)

Aspect Ratio:

16:9

Backlight Technology:

LED

Display Screen Coating:

Antiglare with 3H hardness

Panel Type :

In-Plane switching Technology

Maximum Preset Resolution:

1920 x 1080 at 60Hz

Viewing Angle:

(178° vertical / 178° horizontal)

Contrast Ratio:

1000: 1 (typical)

4 Million: 1 (Dynamic)

Pixel Pitch:

0.248 mm x 0.248 mm

Pixel Per Inch (PPI):

102

Brightness:

250 cd/m² (typical)

Response Time:

6ms (gray to gray))

Wireless Charging Feature:

NA

G-SYNC Support:

NA

PbP/PiP:

PbP (No)

PiP (No)

Daisy Chain Availability:

No

Dell Display Manager Compatibility:

Yes

Remote Asset Management:

Yes, via Dell Command |Monitor

Color Support:

Connectivity

1 x DP (ver 1.2)

1 x HDMI (ver 1.4)

1 x VGA

1 x USB 3.0 port - Upstream

2 x USB 3.0 ports - Side

2 x USB 2.0 ports - Bottom

What's in the box

Monitor with stand

Power cable

1 x DP Cable

1 x VGA Cable

1 x USB 3.0 upstream cable (enables the USB port on the monitor)

Drivers and documentation media

Quick setup guide

Safety Information

Color Gamut (typical): 82% (CIE 1976), 72% (CIE 1931)

Color Depth: 16.7 Million colors

Color Calibration SDK SW:

No

Color Calibration with X-rite colorimeter:

No

Audio Output:

Optional Soundbar - (AC511)

Stand

Height-adjustable stand (130mm)

Tilt (-5° to 21°)

Swivel (45° to 45°)

Pivot (90° clockwise)

Built in cable-management

Flat Panel Mount Interface:

VESA (100 mm)

Built-in Devices

USB3.0 super-Speed Hub (with 1 x USB upstream port, 2 x USB3.0 and 2 x USB2.0 downstream ports)

Security

Security lock slot (cable lock sold separately)

Anti-theft stand lock slot (to panel)

Size and Weight

Dimensions with stand (H x W x D):

Height:

Compressed : 354.4mm (18.81 inches)

Extended : 477.8 mm (13.95 inches)

Width: 498.9 mm (19.64 inches)

Depth: 180.0 mm (7.09 inches)

Dimensions without stand (H x W x D):

Height: 297.3 mm (11.70 inches)

Width: 498.9 mm (19.64 inches)

Depth: 50.3 mm (1.98 inches)

Weight:

With packaging: 6.86 kg (15.09 lb)

Panel only—for VESA mount: 2.81 kg (6.18 lb)

Environmental and Regulatory

Electrical

Voltage Required:

100 to 240 VAC / 50 or 60 Hz ± 3Hz / 1.5 A (typical)

Power Consumption (Operational):

17W (typical) /37W (maximum)**/50.6 kWh (Energy Star)

Environmental

Temperature Range

Operating: 0° to 40°C (32° to 104°F)

Non-operating: -20° to 60° (-4° to 140° F)

Humidity Range

Operating: 10% to 80% (non-condensing)

Non-Operating:5% to 90% (non-condensing)

Power Consumption Stand by / Sleep:

Less than 0.3W

Altitude

Operating: 5,000 m (16,400 ft) max

Non-Operating: 12,191 m (40,000 ft) max

Compliance and Standards

ENERGY STAR

EPEAT Gold

TCO Certified Displays

RoHS Compliant

[Product Safety, EMC and Environmental Datasheets](#)

[Dell Regulatory Compliance Home Page](#)

[Dell and the Environment](#)

Warranty

3 years Advanced Exchange Service and Premium Panel Guarantee